


# EASY: LINE LOWBAY



Teknoware Easy Line Lowbay is a versatile and cost-effective emergency light. It provides a long and narrow light pattern that illuminates corridors and escape routes efficiently.

Easy Line Lowbay can easily be surface or semi-flush mounted thanks to its practical design. Easy's wide product family offers an ideal choice when you want a single fixture for your entire property's needs.

for escape routes

5-year warranty

installation height: up to 4 metres

self-contained or centrally supplied depending on model

protection rating: IP40 (or IP54 with an additional seal, sold separately)

standard installation: either surface or semi-flush mounted, suspended installation with a separate mounting bracket

self-contained emergency lights use a LiFePO<sub>4</sub> battery

The product codes starting with letter Y include an individually packed luminaire. The product codes starting with TW include the luminaire only.

## SELF-CONTAINED EMERGENCY LIGHTS WITH BATTERY AND SELF-TESTING

We reserve the rights to make modifications without notice.

Copyright © 2021 Teknoware. All rights reserved.

Date: January 02, 2021 | Source:

[www.teknoware.com/en/emergency-lighting/emergency-lights/emergency-light-product-families/easy-line-lowbay](http://www.teknoware.com/en/emergency-lighting/emergency-lights/emergency-light-product-families/easy-line-lowbay)



Teknoware Oy | P.O. Box 19, 15101 Lahti | Ilmarisentie 8, 15200 Lahti Finland  
Tel +358 3 883 020 | VAT-number FI01494751 | [teknoware.com](http://teknoware.com) | [emexit@teknoware.com](mailto:emexit@teknoware.com)

Product Code	Nominal Supply Voltage	Feature	Backup (h)
TWTB252WM	220-240 V, 50/60 Hz AC	Lumi Test	1
TWTB253WM	220-240 V, 50/60 Hz AC	Lumi Test	3

## SELF-CONTAINED EMERGENCY LIGHTS WITH BATTERY AND WIRELESS CENTRAL MONITORING

Product Code	Nominal Supply Voltage	Feature	Backup (h)
TWTB252WA	220-240 V, 50/60 Hz AC	Aalto Control	1
TWTB253WA	220-240 V, 50/60 Hz AC	Aalto Control	3

## ADDRESSABLE 230 V CENTRALLY SUPPLIED EMERGENCY LIGHTS

Product Code	Nominal Supply Voltage	Feature
TWTB251WK	220-240 V, 50/60 Hz AC, DC	Intelligent Controller, Tapsa Control

We reserve the rights to make modifications without notice.


Copyright © 2021 Teknoware. All rights reserved.

Date: January 02, 2021 | Source:

[www.teknoware.com/en/emergency-lighting/emergency-lights/emergency-light-product-families/easy-line-lowbay](http://www.teknoware.com/en/emergency-lighting/emergency-lights/emergency-light-product-families/easy-line-lowbay)



# EASY LINE LOWBAY EMERGENCY LIGHT TWTB251WK



## Addressable 230 V centrally supplied emergency light

Teknoware Easy Line Lowbay is a versatile and cost-effective emergency light. It provides a long and narrow light pattern that illuminates corridors and escape routes efficiently.

Easy Line Lowbay can easily be surface or semi-flush mounted thanks to its practical design. Easy's wide product family offers an ideal choice when you want a single fixture for your entire property's needs. Teknoware Easy Line Lowbay is a versatile and cost-effective emergency light. It provides a long and narrow light pattern that illuminates corridors and escape routes efficiently.


Easy Line Lowbay can easily be surface or semi-flush mounted thanks to its practical design. Easy's wide product family offers an ideal choice when you want a single fixture for your entire property's needs.

Product Code	TWTB251WK
Feature	Intelligent Controller, Tapsa Control
Mounting (standard)	ceiling, surface, recess
Customs Code	94056080
GTIN Code	6438045026701
ETIM Product Class	EC001957
Length	265 mm
Width	137 mm
Height	53 mm
Weight	0.45 kg
Max Input Power VA	7,2 VA
Max Input Power W	3,6 W
Nominal Supply Voltage	220-240 V, 50/60 Hz AC, DC
Protection Class	II
IP Class	IP40
Temperature Range Min - Max	-30...+50 °C
Glow Wire Test of Plastic Materials	650 °C
Light Source	LED
Body Material	plastic
Colour	RAL9003
Electrical Installation	2/3 x 2,5 mm <sup>2</sup>
Luminous Flux	170 lm

## Emergency lighting for escape routes (ceiling mounting)

Table of 1 lux for escape routes in the middle line according to the norm EN 1838.

Level of measurement 0,02 m, measurement result with battery operation.



R1 distance from wall (X axis)  
 R2 installation distance between lights (X axis)  
 R4 distance from wall (Y axis)  
**TWTB251WK**

Mounting height (m)	Below the light lux	R1 (m)	R2 (m)	R4 (m)
		1 lux	1 lux	1 lux
2,5	6.5	7	17	1
3	4.5	8	19	1
4	2.5	8	23	1

## OPTIONAL ACCESSORIES:

## OTHER ACCESSORIES FOR EMERGENCY LIGHTS



Product Code	Product Name	Compatible Product Groups
TWTB110	Easy Combo IP54 gasket TWTB110	Other Accessories for Emergency Exit Lights

## OPTIONAL MOUNTING ACCESSORIES FOR EMERGENCY EXIT LIGHTS



Product Code	Product Name	Compatible Product Groups
TWTB101	Easy Combo recess mounting frame TWTB101	Easy: Combo Emergency / Exit Light, Easy: Combo Emergency / Exit Light
TWTB103	Easy Combo flag bracket TWTB103	Easy: Combo Emergency / Exit Light, Easy: Combo Emergency / Exit Light
TWTB104	Easy Combo ceiling bracket TWTB104	Easy: Combo Emergency / Exit Light, Easy: Combo Emergency / Exit Light

We reserve the rights to make modifications without notice.  
 Copyright © 2021 Teknoware. All rights reserved.  
 Date: January 02, 2021 | Source:  
[www.teknoware.com/en/emergency-lighting/easy-line-lowbay-emergency-light-twtb251wk](http://www.teknoware.com/en/emergency-lighting/easy-line-lowbay-emergency-light-twtb251wk)




Teknoware Oy | P.O. Box 19, 15101 Lahti | Ilmarisentie 8, 15200 Lahti Finland  
 Tel +358 3 883 020 | VAT-number FI01494751 | [teknoware.com](http://teknoware.com) | [emexit@teknoware.com](mailto:emexit@teknoware.com)

Product Code	Product Name	Compatible Product Groups
TWTB105	Easy Combo suspension bracket TWTB105	Easy: Combo Emergency / Exit Light, Easy: Combo Emergency / Exit Light

We reserve the rights to make modifications without notice.  
Copyright © 2021 Teknoware. All rights reserved.  
Date: January 02, 2021 | Source:  
[www.teknoware.com/en/emergency-lighting/easy-line-lowbay-emergency-light-twtb251wk](http://www.teknoware.com/en/emergency-lighting/easy-line-lowbay-emergency-light-twtb251wk)

Teknoware Oy | P.O. Box 19, 15101 Lahti | Ilmarisentie 8, 15200 Lahti Finland  
Tel +358 3 883 020 | VAT-number FI01494751 | [teknoware.com](http://teknoware.com) | [emexit@teknoware.com](mailto:emexit@teknoware.com)






We reserve the rights to make modifications without notice.  
 Copyright © 2021 Teknoware. All rights reserved.  
 Date: January 02, 2021 | Source:  
[www.teknoware.com/en/emergency-lighting/easy-line-lowbay-emergency-light-twtb251wk](http://www.teknoware.com/en/emergency-lighting/easy-line-lowbay-emergency-light-twtb251wk)

Teknoware Oy | P.O. Box 19, 15101 Lahti | Ilmarisentie 8, 15200 Lahti Finland  
 Tel +358 3 883 020 | VAT-number FI01494751 | [teknoware.com](http://teknoware.com) | [emexit@teknoware.com](mailto:emexit@teknoware.com)



# EASY LINE LOWBAY EMERGENCY LIGHT TWTB252WA



## Self-contained emergency light with 1 h battery and wireless central monitoring

Teknoware Easy Line Lowbay is a versatile and cost-effective emergency light. It provides a long and narrow light pattern that illuminates corridors and escape routes efficiently.

Easy Line Lowbay can easily be surface or semi-flush mounted thanks to its practical design. Easy's wide product family offers an ideal choice when you want a single fixture for your entire property's needs.

Teknoware Easy Line Lowbay is a versatile and cost-effective emergency light. It provides a long and narrow light pattern that illuminates corridors and escape routes efficiently.

Easy Line Lowbay can easily be surface or semi-flush mounted thanks to its practical design. Easy's wide product family offers an ideal choice when you want a single fixture for your entire property's needs.




Product Code	TWTB252WA
Feature	Aalto Control
Mounting (standard)	ceiling, surface, recess
Customs Code	94056080
GTIN Code	6438045026664
ETIM Product Class	EC001957
Length	265 mm
Width	137 mm
Height	53 mm
Weight	0.45 kg
Backup	1 h
Max Input Power VA	8 VA
Nominal Supply Voltage	220-240 V, 50/60 Hz AC
Protection Class	II
IP Class	IP40
Temperature Range Min - Max	0...+35 °C
Glow Wire Test of Plastic Materials	850 °C
Light Source	LED
Body Material	plastic
Colour	RAL9003
Electrical Installation	2/3 x 2,5 mm <sup>2</sup>
Luminous Flux	170 lm

## Emergency lighting for escape routes (ceiling mounting)

Table of 1 lux for escape routes in the middle line according to the norm EN 1838.

Level of measurement 0,02 m, measurement result with battery operation.



R1 distance from wall (X axis)  
 R2 installation distance between lights (X axis)  
 R4 distance from wall (Y axis)  
**TWTB252WA**

Mounting height (m)	Below the light lux	R1 (m)	R2 (m)	R4 (m)
		1 lux	1 lux	1 lux
2,5	6.5	7	17	1
3	4.5	8	19	1
4	2.5	8	23	1

## OPTIONAL ACCESSORIES:

## OTHER ACCESSORIES FOR EMERGENCY LIGHTS



Product Code	Product Name	Compatible Product Groups
TWTB110	Easy Combo IP54 gasket TWTB110	Other Accessories for Emergency Exit Lights

## OPTIONAL MOUNTING ACCESSORIES FOR EMERGENCY EXIT LIGHTS



Product Code	Product Name	Compatible Product Groups
TWTB101	Easy Combo recess mounting frame TWTB101	Easy: Combo Emergency / Exit Light, Easy: Combo Emergency / Exit Light
TWTB103	Easy Combo flag bracket TWTB103	Easy: Combo Emergency / Exit Light, Easy: Combo Emergency / Exit Light
TWTB104	Easy Combo ceiling bracket TWTB104	Easy: Combo Emergency / Exit Light, Easy: Combo Emergency / Exit Light

We reserve the rights to make modifications without notice.  
 Copyright © 2021 Teknoware. All rights reserved.  
 Date: January 02, 2021 | Source:  
[www.teknoware.com/en/emergency-lighting/easy-line-lowbay-emergency-light-twtb252wa](http://www.teknoware.com/en/emergency-lighting/easy-line-lowbay-emergency-light-twtb252wa)




Teknoware Oy | P.O. Box 19, 15101 Lahti | Ilmarisentie 8, 15200 Lahti Finland  
 Tel +358 3 883 020 | VAT-number FI01494751 | [teknoware.com](http://teknoware.com) | [emexit@teknoware.com](mailto:emexit@teknoware.com)

Product Code	Product Name	Compatible Product Groups
TWTB105	Easy Combo suspension bracket TWTB105	Easy: Combo Emergency / Exit Light, Easy: Combo Emergency / Exit Light

We reserve the rights to make modifications without notice.  
Copyright © 2021 Teknoware. All rights reserved.  
Date: January 02, 2021 | Source:  
[www.teknoware.com/en/emergency-lighting/easy-line-lowbay-emergency-light-twtb252wa](http://www.teknoware.com/en/emergency-lighting/easy-line-lowbay-emergency-light-twtb252wa)

Teknoware Oy | P.O. Box 19, 15101 Lahti | Ilmarisentie 8, 15200 Lahti Finland  
Tel +358 3 883 020 | VAT-number FI01494751 | [teknoware.com](http://teknoware.com) | [emexit@teknoware.com](mailto:emexit@teknoware.com)






We reserve the rights to make modifications without notice.  
 Copyright © 2021 Teknoware. All rights reserved.  
 Date: January 02, 2021 | Source:  
[www.teknoware.com/en/emergency-lighting/easy-line-lowbay-emergency-light-twtb252wa](http://www.teknoware.com/en/emergency-lighting/easy-line-lowbay-emergency-light-twtb252wa)

Teknoware Oy | P.O. Box 19, 15101 Lahti | Ilmarisentie 8, 15200 Lahti Finland  
 Tel +358 3 883 020 | VAT-number FI01494751 | [teknoware.com](http://teknoware.com) | [emexit@teknoware.com](mailto:emexit@teknoware.com)



# EASY LINE LOWBAY EMERGENCY LIGHT TWTB252WM



## Self-contained emergency light with 1 h battery and Lumi Test self-testing

Teknoware Easy Line Lowbay is a versatile and cost-effective emergency light. It provides a long and narrow light pattern that illuminates corridors and escape routes efficiently.

Easy Line Lowbay can easily be surface or semi-flush mounted thanks to its practical design. Easy's wide product family offers an ideal choice when you want a single fixture for your entire property's needs. Teknoware Easy Line Lowbay is a versatile and cost-effective emergency light. It provides a long and narrow light pattern that illuminates corridors and escape routes efficiently.


Easy Line Lowbay can easily be surface or semi-flush mounted thanks to its practical design. Easy's wide product family offers an ideal choice when you want a single fixture for your entire property's needs.

Product Code	TWTB252WM
Feature	Lumi Test
Mounting (standard)	ceiling, surface, recess
Customs Code	94056080
GTIN Code	6438045026671
ETIM Product Class	EC001957
Length	265 mm
Width	137 mm
Height	53 mm
Weight	0.45 kg
Backup	1 h
Max Input Power VA	8 VA
Nominal Supply Voltage	220-240 V, 50/60 Hz AC
Protection Class	II
IP Class	IP40
Temperature Range Min - Max	0...+35 °C
Glow Wire Test of Plastic Materials	850 °C
Light Source	LED
Body Material	plastic
Colour	RAL9003
Electrical Installation	2/3 x 2,5 mm <sup>2</sup>
Luminous Flux	170 lm

## Emergency lighting for escape routes (ceiling mounting)

Table of 1 lux for escape routes in the middle line according to the norm EN 1838.

Level of measurement 0,02 m, measurement result with battery operation.



- R1 distance from wall (X axis)
- R2 installation distance between lights (X axis)
- R4 distance from wall (Y axis)

## TWTB252WM

Mounting height (m)	Below the light lux	R1 (m)	R2 (m)	R4 (m)
		1 lux	1 lux	1 lux
2,5	6.5	7	17	1
3	4.5	8	19	1
4	2.5	8	23	1

## OPTIONAL ACCESSORIES:

### OTHER ACCESSORIES FOR EMERGENCY LIGHTS



Product Code	Product Name	Compatible Product Groups
TWTB110	Easy Combo IP54 gasket TWTB110	Other Accessories for Emergency Exit Lights

### OPTIONAL MOUNTING ACCESSORIES FOR EMERGENCY EXIT LIGHTS



Product Code	Product Name	Compatible Product Groups
TWTB101	Easy Combo recess mounting frame TWTB101	Easy: Combo Emergency / Exit Light, Easy: Combo Emergency / Exit Light
TWTB103	Easy Combo flag bracket TWTB103	Easy: Combo Emergency / Exit Light, Easy: Combo Emergency / Exit Light
TWTB104	Easy Combo ceiling bracket TWTB104	Easy: Combo Emergency / Exit Light, Easy: Combo Emergency / Exit Light

We reserve the rights to make modifications without notice.  
 Copyright © 2021 Teknoware. All rights reserved.  
 Date: January 02, 2021 | Source:  
[www.teknoware.com/en/emergency-lighting/easy-line-lowbay-emergency-light-twtb252wm](http://www.teknoware.com/en/emergency-lighting/easy-line-lowbay-emergency-light-twtb252wm)



Teknoware Oy | P.O. Box 19, 15101 Lahti | Ilmarisentie 8, 15200 Lahti Finland  
 Tel +358 3 883 020 | VAT-number FI01494751 | [teknoware.com](http://teknoware.com) | [emexit@teknoware.com](mailto:emexit@teknoware.com)


Product Code	Product Name	Compatible Product Groups
TWTB105	Easy Combo suspension bracket TWTB105	Easy: Combo Emergency / Exit Light, Easy: Combo Emergency / Exit Light

We reserve the rights to make modifications without notice.  
Copyright © 2021 Teknoware. All rights reserved.  
Date: January 02, 2021 | Source:  
[www.teknoware.com/en/emergency-lighting/easy-line-lowbay-emergency-light-twtb252wm](http://www.teknoware.com/en/emergency-lighting/easy-line-lowbay-emergency-light-twtb252wm)

Teknoware Oy | P.O. Box 19, 15101 Lahti | Ilmarisentie 8, 15200 Lahti Finland  
Tel +358 3 883 020 | VAT-number FI01494751 | [teknoware.com](http://teknoware.com) | [emexit@teknoware.com](mailto:emexit@teknoware.com)








We reserve the rights to make modifications without notice.  
 Copyright © 2021 Teknoware. All rights reserved.  
 Date: January 02, 2021 | Source:  
[www.teknoware.com/en/emergency-lighting/easy-line-lowbay-emergency-light-twtb252wm](http://www.teknoware.com/en/emergency-lighting/easy-line-lowbay-emergency-light-twtb252wm)

Teknoware Oy | P.O. Box 19, 15101 Lahti | Ilmarisentie 8, 15200 Lahti Finland  
 Tel +358 3 883 020 | VAT-number FI01494751 | [teknoware.com](http://teknoware.com) | [emexit@teknoware.com](mailto:emexit@teknoware.com)



# EASY LINE LOWBAY EMERGENCY LIGHT TWTB253WA



## Self-contained emergency light with 3 h battery and wireless central monitoring

Teknoware Easy Line Lowbay is a versatile and cost-effective emergency light. It provides a long and narrow light pattern that illuminates corridors and escape routes efficiently.

Easy Line Lowbay can easily be surface or semi-flush mounted thanks to its practical design. Easy's wide product family offers an ideal choice when you want a single fixture for your entire property's needs. Teknoware Easy Line Lowbay is a versatile and cost-effective emergency light. It provides a long and narrow light pattern that illuminates corridors and escape routes efficiently.

Easy Line Lowbay can easily be surface or semi-flush mounted thanks to its practical design. Easy's wide product family offers an ideal choice when you want a single fixture for your entire property's needs.

Product Code	TWTB253WA
Feature	Aalto Control
Mounting (standard)	ceiling, surface, recess
Customs Code	94056080
GTIN Code	6438045026688
ETIM Product Class	EC001957
Length	265 mm
Width	137 mm
Height	53 mm
Weight	0.45 kg
Backup	3 h
Max Input Power VA	8 VA
Nominal Supply Voltage	220-240 V, 50/60 Hz AC
Protection Class	II
IP Class	IP40
Temperature Range Min - Max	0...+35 °C
Glow Wire Test of Plastic Materials	850 °C
Light Source	LED
Body Material	plastic
Colour	RAL9003
Electrical Installation	2/3 x 2,5 mm <sup>2</sup>
Luminous Flux	170 lm

## Emergency lighting for escape routes (ceiling mounting)

Table of 1 lux for escape routes in the middle line according to the norm EN 1838.

Level of measurement 0,02 m, measurement result with battery operation.

We reserve the rights to make modifications without notice.

Copyright © 2021 Teknoware. All rights reserved.


Date: January 02, 2021 | Source:

[www.teknoware.com/en/emergency-lighting/easy-line-lowbay-emergency-light-twtb253wa](http://www.teknoware.com/en/emergency-lighting/easy-line-lowbay-emergency-light-twtb253wa)



Teknoware Oy | P.O. Box 19, 15101 Lahti | Ilmarisentie 8, 15200 Lahti Finland

Tel +358 3 883 020 | VAT-number FI01494751 | [teknoware.com](http://teknoware.com) | [emexit@teknoware.com](mailto:emexit@teknoware.com)



R1 distance from wall (X axis)

R2 installation distance between lights (X axis)

R4 distance from wall (Y axis)

## TWTB253WA

Mounting height (m)	Below the light lux	R1 (m)	R2 (m)	R4 (m)
		1 lux	1 lux	1 lux
2,5	6.5	7	17	1
3	4.5	8	19	1
4	2.5	8	23	1

## OPTIONAL ACCESSORIES:

### OTHER ACCESSORIES FOR EMERGENCY LIGHTS



Product Code	Product Name	Compatible Product Groups
TWTB110	Easy Combo IP54 gasket TWTB110	Other Accessories for Emergency Exit Lights

### OPTIONAL MOUNTING ACCESSORIES FOR EMERGENCY EXIT LIGHTS



Product Code	Product Name	Compatible Product Groups
TWTB101	Easy Combo recess mounting frame TWTB101	Easy: Combo Emergency / Exit Light, Easy: Combo Emergency / Exit Light
TWTB103	Easy Combo flag bracket TWTB103	Easy: Combo Emergency / Exit Light, Easy: Combo Emergency / Exit Light
TWTB104	Easy Combo ceiling bracket TWTB104	Easy: Combo Emergency / Exit Light, Easy: Combo Emergency / Exit Light

We reserve the rights to make modifications without notice.

Copyright © 2021 Teknoware. All rights reserved.

Date: January 02, 2021 | Source:

[www.teknoware.com/en/emergency-lighting/easy-line-lowbay-emergency-light-twtb253wa](http://www.teknoware.com/en/emergency-lighting/easy-line-lowbay-emergency-light-twtb253wa)



Teknoware Oy | P.O. Box 19, 15101 Lahti | Ilmarisentie 8, 15200 Lahti Finland


Tel +358 3 883 020 | VAT-number FI01494751 | [teknoware.com](http://teknoware.com) | [emexit@teknoware.com](mailto:emexit@teknoware.com)

Product Code	Product Name	Compatible Product Groups
TWTB105	Easy Combo suspension bracket TWTB105	Easy: Combo Emergency / Exit Light, Easy: Combo Emergency / Exit Light

We reserve the rights to make modifications without notice.  
Copyright © 2021 Teknoware. All rights reserved.  
Date: January 02, 2021 | Source:  
[www.teknoware.com/en/emergency-lighting/easy-line-lowbay-emergency-light-twtb253wa](http://www.teknoware.com/en/emergency-lighting/easy-line-lowbay-emergency-light-twtb253wa)

Teknoware Oy | P.O. Box 19, 15101 Lahti | Ilmarisentie 8, 15200 Lahti Finland  
Tel +358 3 883 020 | VAT-number FI01494751 | [teknoware.com](http://teknoware.com) | [emexit@teknoware.com](mailto:emexit@teknoware.com)






We reserve the rights to make modifications without notice.  
 Copyright © 2021 Teknoware. All rights reserved.  
 Date: January 02, 2021 | Source:  
[www.teknoware.com/en/emergency-lighting/easy-line-lowbay-emergency-light-twtb253wa](http://www.teknoware.com/en/emergency-lighting/easy-line-lowbay-emergency-light-twtb253wa)

Teknoware Oy | P.O. Box 19, 15101 Lahti | Ilmarisentie 8, 15200 Lahti Finland  
 Tel +358 3 883 020 | VAT-number FI01494751 | [teknoware.com](http://teknoware.com) | [emexit@teknoware.com](mailto:emexit@teknoware.com)



# EASY LINE LOWBAY EMERGENCY LIGHT TWTB253WM



## Self-contained emergency light with 3 h battery and Lumi Test self-testing

Teknoware Easy Line Lowbay is a versatile and cost-effective emergency light. It provides a long and narrow light pattern that illuminates corridors and escape routes efficiently.

Easy Line Lowbay can easily be surface or semi-flush mounted thanks to its practical design. Easy's wide product family offers an ideal choice when you want a single fixture for your entire property's needs. Teknoware Easy Line Lowbay is a versatile and cost-effective emergency light. It provides a long and narrow light pattern that illuminates corridors and escape routes efficiently.

Easy Line Lowbay can easily be surface or semi-flush mounted thanks to its practical design. Easy's wide product family offers an ideal choice when you want a single fixture for your entire property's needs.


Product Code	TWTB253WM
Feature	Lumi Test
Mounting (standard)	ceiling, surface, recess
Customs Code	94056080
GTIN Code	6438045026695
ETIM Product Class	EC001957
Length	265 mm
Width	137 mm
Height	53 mm
Weight	0.45 kg
Backup	3 h
Max Input Power VA	8 VA
Nominal Supply Voltage	220-240 V, 50/60 Hz AC
Protection Class	II
IP Class	IP40
Temperature Range Min - Max	0...+35 °C
Glow Wire Test of Plastic Materials	850 °C
Light Source	LED
Body Material	plastic
Colour	RAL9003
Electrical Installation	2/3 x 2,5 mm <sup>2</sup>
Luminous Flux	170 lm

## Emergency lighting for escape routes (ceiling mounting)

Table of 1 lux for escape routes in the middle line according to the norm EN 1838.

Level of measurement 0,02 m, measurement result with battery operation.





R1 distance from wall (X axis)  
 R2 installation distance between lights (X axis)  
 R4 distance from wall (Y axis)  
**TWTB253WM**

Mounting height (m)	Below the light lux	R1 (m)	R2 (m)	R4 (m)
		1 lux	1 lux	1 lux
2,5	6.5	7	17	1
3	4.5	8	19	1
4	2.5	8	23	1

## OPTIONAL ACCESSORIES:

## OTHER ACCESSORIES FOR EMERGENCY LIGHTS



Product Code	Product Name	Compatible Product Groups
TWTB110	Easy Combo IP54 gasket TWTB110	Other Accessories for Emergency Exit Lights

## OPTIONAL MOUNTING ACCESSORIES FOR EMERGENCY EXIT LIGHTS



Product Code	Product Name	Compatible Product Groups
TWTB101	Easy Combo recess mounting frame TWTB101	Easy: Combo Emergency / Exit Light, Easy: Combo Emergency / Exit Light
TWTB103	Easy Combo flag bracket TWTB103	Easy: Combo Emergency / Exit Light, Easy: Combo Emergency / Exit Light
TWTB104	Easy Combo ceiling bracket TWTB104	Easy: Combo Emergency / Exit Light, Easy: Combo Emergency / Exit Light

We reserve the rights to make modifications without notice.  
 Copyright © 2021 Teknoware. All rights reserved.  
 Date: January 02, 2021 | Source:  
[www.teknoware.com/en/emergency-lighting/easy-line-lowbay-emergency-light-twtb253wm](http://www.teknoware.com/en/emergency-lighting/easy-line-lowbay-emergency-light-twtb253wm)




Teknoware Oy | P.O. Box 19, 15101 Lahti | Ilmarisentie 8, 15200 Lahti Finland  
 Tel +358 3 883 020 | VAT-number FI01494751 | [teknoware.com](http://teknoware.com) | [emexit@teknoware.com](mailto:emexit@teknoware.com)

Product Code	Product Name	Compatible Product Groups
TWTB105	Easy Combo suspension bracket TWTB105	Easy: Combo Emergency / Exit Light, Easy: Combo Emergency / Exit Light

We reserve the rights to make modifications without notice.  
Copyright © 2021 Teknoware. All rights reserved.  
Date: January 02, 2021 | Source:  
[www.teknoware.com/en/emergency-lighting/easy-line-lowbay-emergency-light-twtb253wm](http://www.teknoware.com/en/emergency-lighting/easy-line-lowbay-emergency-light-twtb253wm)

Teknoware Oy | P.O. Box 19, 15101 Lahti | Ilmarisentie 8, 15200 Lahti Finland  
Tel +358 3 883 020 | VAT-number FI01494751 | [teknoware.com](http://teknoware.com) | [emexit@teknoware.com](mailto:emexit@teknoware.com)





We reserve the rights to make modifications without notice.  
 Copyright © 2021 Teknoware. All rights reserved.  
 Date: January 02, 2021 | Source:  
[www.teknoware.com/en/emergency-lighting/easy-line-lowbay-emergency-light-twtb253wm](http://www.teknoware.com/en/emergency-lighting/easy-line-lowbay-emergency-light-twtb253wm)

Teknoware Oy | P.O. Box 19, 15101 Lahti | Ilmarisentie 8, 15200 Lahti Finland  
 Tel +358 3 883 020 | VAT-number FI01494751 | [teknoware.com](http://teknoware.com) | [emexit@teknoware.com](mailto:emexit@teknoware.com)

