



ТЕХНИЧЕСКОЕ ОПИСАНИЕ

AIMOL X-Cool Plus 46

AIMOL X-Cool Plus 46 –

()

2-8%

- 2-3%-
- 3-5%-
- 5-7%-
- 3-6%-
- 4-8%-



AIMOL X-Cool Plus 46

- DIN 51385 2.1 (SEM)
- ISO 6743/7 L-MAB

AIMOL X-Cool Plus 46





ТЕХНИЧЕСКОЕ ОПИСАНИЕ

AIMOL X-Cool Plus 46

AIMOL X-Cool Plus 46

25° , 50° 100-300 ppm 5-
60 . 50° 100-300 ppm 30-
TDS- 0,1 / . % = 5%.

0,97. x 0,95;
: % = 5%.
AIMOL X-Cool Plus 46 -30° 5%-
(280 ppm) AIMOL X-Cool Plus 46 0 +35°

X-Cool Plus 46	
20°C, /	0.906
, %	62
50° ,	42.4
, %	
20° , / ³	0.9172

5% (280 ppm)

X-Cool Plus 46	
pH	9.6
45	
-4 (1583-89)	
20±5° ,	40
8	
20±5° ,	0

AIMOL X-Cool Plus 46 –

AIMOL,



ТЕХНИЧЕСКОЕ ОПИСАНИЕ

AIMOL X-Cool Plus 46

AIM b.v.

ANGLO INTERNATIONAL MINING B.V.
Haringvliet 543, 3011 ZP Rotterdam
The Netherlands
T +31 (0)10 28 27 927
info@aimol.nl

www.aimol.nl
www.aimol.ru

« 127550 »
44, 2
+7 (495) 602 01 74
info@aimol.ru